

## GENERAL DESCRIPTION

**PRODUCT NAME:** CLASSIC Country Manor Shale  
**DESCRIPTION:** Aluminum Shake Roofing System  
**USE:** Residential and light commercial roofs and mansards with elevations up to 30" (9114mm)

**CANADA DISTRIBUTOR:**

Classic Products Roofing Systems Inc.  
 275 Watline Ave., Mississauga, ON L4Z 1P3  
**1-866-969-7663**  
 info@classicproducts.ca | www.classicproducts.ca

**MANUFACTURER:** Isaiah Industries Inc.

## FINISH

Country Manor Shake is coated with a baked-on protective primer and Kynar 500 or Hylar 5000 top coat to provide a high quality finish.

Kynar 500 and Hylar 5000 are trade names for polyvinylidene flouride resin. Panel backs are finished with a protective clear coat.

Also available in Thermobond Custom Colours.

## CLASSIC COUNTRY MANOR SHAKE



### Four-Way Interlocking Design

**Exposure Height: 12"**  
**Exposure Width: 48"**  
**Thickness: .019"/.483 mm**  
**Weight/Square: 46 lbs**

» Flashings and matching coilstock are made of .019"/.483mm 3105 H26 aluminum alloy sheet stock with a yield strength of 26 000 psi and tensile strength of 22 000 psi.

- » All pre-formed panels including pre-formed accessories and flashing
- » Metal Construction Association Certified Premium Roofing Panels
- » Optional fitted foam inserts for high traffic areas
- » LEED Credit Eligible

## INSTALLATION

- » **Minimum Pitch 4:12 (snow areas)**
- » Applied over minimum 3/8" decking
- » May be applied over existing composition shingles (single or multi-layer).
- » Entire roof must be covered with at least one layer of 30 lb felt or equivalent
- » Continuous nailing flange for easy application
- » Concealed vertical lock for "seamless" looking pattern

**Scope:** The scope of work includes but is not limited to, the installation of all pre-formed panels, pre-formed accessories and field formed accessories such as miscellaneous flashings and attaching devices as well as sealant.

**Note on Dissimilar Materials:** Aluminum materials should not be installed in contact with dissimilar metals, or other corrosive nonmetallic materials that might be wet continually. Dissimilar materials should be painted or otherwise protected when in contact with aluminum. Do not permit water from copper flashing to drain over aluminum products.